

Application Serial No: 10/583,025  
Responsive to the Office Action mailed on: December 23, 2008

RECEIVED  
CENTRAL FAX CENTER

MAR 23 2009

**IN THE CLAIMS**

**Amendments To The Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently Amended) An ultrasonic diagnostic apparatus comprising: a plurality of transducers for transmitting and receiving an ultrasonic wave; transmission pulse generators for generating pulses that allow the transducers to transmit the ultrasonic wave; a transmission power source for supplying power to the transmission pulse generators; and an output side capacitor for stabilizing a voltage of the transmission power source,

the transmission power source including: a plurality of mode-specific step-up power sources for outputting a voltage corresponding to each of a plurality of signal processing modes; a power source side capacitor connected to an output side of each of the mode-specific step-up power sources for stabilizing the voltage; and a mode changeover switch provided between the output side of the mode-specific step-up power sources and the output side capacitor for switching between the mode-specific step-up power sources that supply power to the transmission pulse generators,

wherein the transmission power source further includes:

a power supplying power source connected to an input side of the mode-specific step-up power sources for supplying power; and

a power regeneration capacitor with a larger capacity than that of the output side capacitor, one electrode terminal of which is connected to a connection point between the power supplying power source and the input side of the mode-specific step-up power sources and the mode changeover switch, and the other electrode terminal of which is connected to ground, and

the mode changeover switch is capable of connecting the power regeneration capacitor, instead of the output side of each of the mode-specific step-up power sources, to the output side capacitor.

Application Serial No: 10/583,025

Responsive to the Office Action mailed on: December 23, 2008

2. (Currently Amended) ~~The ultrasonic diagnostic apparatus according to claim 1, comprising a plurality of power regeneration capacitors;~~

An ultrasonic diagnostic apparatus comprising a plurality of transducers for transmitting and receiving an ultrasonic wave; transmission pulse generators for generating pulses that allow the transducers to transmit the ultrasonic wave; a transmission power source for supplying power to the transmission pulse generators; and an output side capacitor for stabilizing a voltage of the transmission power source,

the transmission power source including: a plurality of mode-specific step-down power sources for outputting a voltage corresponding to each of a plurality of signal processing modes; a power source side capacitor connected to an output side of each of the mode-specific step-down power sources for stabilizing the voltage; and a mode changeover switch provided between the output side of the mode-specific step-down power sources and the output side capacitor for switching between the mode-specific step-down power sources that supply power to the transmission pulse generators,

wherein the transmission power source further includes:

a power supplying power source connected to an input side of the mode-specific step-down power sources for supplying power;

a power regeneration capacitor, including a plurality of capacitors, with a larger capacity than that of the output side capacitor, one electrode terminal of which is connected to a connection point between the power supplying power source and the input side of the mode-specific step-down power sources and the mode changeover switch, and the other electrode terminal of which is connected to ground; and

a switch for switching between a connection point between an output side of the power supplying power source and the power regeneration capacitor and the input side of the mode-specific step-down power sources; and

the power regeneration switch is provided that is constituted to achieve a state in which the plurality of power regeneration capacitors are connected in cascade with respect to the input side of each of the mode-specific step-down power sources and a state in which the plurality of power regeneration capacitors are connected in parallel with respect to the mode changeover switch.

Application Serial No: 10/583,025

Responsive to the Office Action mailed on: December 23, 2008

3. (Original) The ultrasonic diagnostic apparatus according to claim 2, wherein when the mode changeover switch connects the output side capacitor to the output side of each of the mode-specific power sources, the power regeneration switch is controlled to connect the plurality of power regeneration capacitors in cascade with respect to each of the mode-specific power sources and the power source side capacitor.

4. (Previously Presented) The ultrasonic diagnostic apparatus according to claim 2, wherein when the mode changeover switch connects the output side capacitor to the plurality of power regeneration capacitors, the power regeneration switch is controlled to connect the plurality of power regeneration capacitors in parallel with respect to the mode changeover switch.

5. (Previously Presented) The ultrasonic diagnostic apparatus according to claim 1, wherein a photo MOS relay is used as the mode changeover switch.

6. (Previously Presented) The ultrasonic diagnostic apparatus according to claim 1, wherein a MEMS (Micro Electro Mechanical Systems) relay is used as the mode changeover switch.

7. (Previously Presented) The ultrasonic diagnostic apparatus according to claim 1, wherein a DC-DC converter is used as the transmission power source.

8. (Previously Presented) The ultrasonic diagnostic apparatus according to claim 3, wherein when the mode changeover switch connects the output side capacitor to the plurality of power regeneration capacitors, the power regeneration switch is controlled to connect the plurality of power regeneration capacitors in cascade with respect to the mode changeover switch.